


Outlet valves

Equipment and accessories for the Fillflex system

FILLFLEX

– the flexible filling machines



One of the many advantages with the Fillflex system is the possibility to control the whole filling process, down to the last detail. By equipping your filler with a pneumatic outlet valve, you can also handle “difficult” products with foaming properties or with solid particles.

Foaming products are easily filled with our pneumatic bottom filler where a filling lance is lowered into the container prior to filling. The whole filling sequence can then be optimized with the fillers built-in control program.

An outlet valve also gives smoother operation, without the risk of dripping. In addition to this, the filled amount stay very accurate, even at high production rates.



Cone valve, internal, pneumatic

Wide opening mushroom valve. The entire cone passes the T-connection. With sensor that opens the valve before filling starts.

Order number:

TFV20101-2525-08	(8 mm connection)
TFV20101-2525-10	(10 mm connection)
TFV20101-2525-12	(12 mm connection)
TFV20101-2525-14	(14 mm connection)
TFV20101-2525-16	(16 mm connection)
TFV20101-2538-18	(18 mm connection)
TFV20101-2538-20	(20 mm connection)
TFV20101-2538-25	(25 mm connection)
TFV20101-3851-38	(38 mm connection)



Hose valve, pneumatic

An allround valve for most medias.

Order number:

TFV20121-25/12	(25 mm connection SMS; 12 mm hose)
TFV20121-25/16	(25 mm connection SMS; 16 mm hose)
TFV20121-25/20	(25 mm connection SMS; 20 mm hose)
TFV20121-25/25	(25 mm connection SMS; 25 mm hose)
TFV20121-38/38	(38 mm connection SMS; 38 mm hose)




Hose valve, pneumatic

With large opening. For big solids.

Order number:

TFV20125-25/25-1	(25 mm connection SMS; 25 mm hose)
TFV20125-38/38-1	(38 mm connection SMS; 38 mm hose)



Filling lance, pneumatic

A filling lance is used for filling foaming products. Length: standard 300 mm. Connection 25 mm SMS.

Order number:

TFV20130-10	(outside diameter, lance 10 mm)
TFV20130-12	(outside diameter, lance 12 mm)
TFV20130-14	(outside diameter, lance 14 mm)
TFV20130-16	(outside diameter, lance 16 mm)
TFV20130-18	(outside diameter, lance 18 mm)
TFV20130-20	(outside diameter, lance 20 mm)
TFV20130-22	(outside diameter, lance 22 mm)
TFV20130-25	(outside diameter, lance 25 mm)



Piston valve, pneumatic

A piston valve is, among other things, used for viscous products which also could contain particles.

Connection 38 mm SMS.

Order number:
TFV20140-38/38




Bottom filler

For Fillflex Compact TF5500C. Pneumatically controlled.

Order number:
TFA10100

Add:
Filling lance (order no. TFV20130)
Bottom/valve control (order no. TFA10160)



Valve control

For opening/closure of TFV pneumatic valves.

Order number:
TFA10155



Bottom filler and valve control

For opening/closure of TFV pneumatic valves and TFA 10100 bottom filler.

Order number:
TFA10160